

Séria F



GB8AFL

GB8FL

GB9FL

GB11FL

GB14FL

GB600EL

ŠPECIFIKÁCIE

Popis	Jednotka	GB8AF	GB8F	GB9F	GB11F	GB14F	GB170E	GB220E	GB300E	GB320E	GB500E	GB530E	GB600E
Prietok oleja	lit/min	120~150	120~150	120~150	160~240	190~250	90~120	125~150	150~190	160~200	180~250	190~280	250~340
	gpm	32~40	32~40	32~40	42~61	50~66	24~32	33~40	40~50	42~52	48~67	50~74	66~74
Prevádzkový tlak oleja	bar	160~180	160~180	160~180	160~180	160~185	150~170	160~180	160~180	160~180	165~185	165~185	170~190
	psi	2,352~2,646	2,352~2,646	2,352~2,646	2,352~2,646	2,352~2,719	2,205~2,499	2,352~2,646	2,352~2,646	2,352~2,646	2,410~2,719	2,410~2,719	2,465~2,755
Uvoľnenie systému	bar	210	210	210	210	210	200	210	210	210	210	210	220
	psi	3,045	3,045	3,045	3,045	3,045	2,900	3,045	3,045	3,045	3,045	3,045	3,190
Úderov za minútu	bpm	350~680	300~600	280~550	280~450	280~400	400~750	350~700	300~650	300~500	260~450	120~340	100~250
Energia nárazu	joule	4,500	4,600	5,100	6,100	9,500	2,800	4,800	6,000	6,100	9,000	10,500	12,500
	foot-pounds	3,319	3,392	3,761	4,499	7,007	2,065	3,540	4,425	4,499	6,638	7,744	9,220
Priemer nástroja	mm	135	137	140	155	160	120	135	150	150	160	165	180
	inch	5.31	5.39	5.51	6.1	6.3	4.72	5.31	5.9	5.9	6.3	6.5	7.1
Priemer olejovej hadice	mm	25	25	25	32	32	19	25	25	32	32	32	32
	inch	1	1	1	1 1/4	1 1/4	3/4	1	1	1 1/4	1 1/4	1 1/4	1 1/4
Tlak plynu utesnenej zadnej hlavy	bar	16.3	16.3	16.3	16.3	16.3	6.2	6.2	6.2	6.2	6.2	16.3	16.3
	psi	236	236	236	236	236	90	90	90	90	90	236	236
Tlak plynu v utesnenom akumulátore	bar	55	55	55	57	57	55	55	55	55	60	60	60
	psi	797	797	797	826	826	797	797	797	797	870	870	870