

Séria T

Modely GB splnia
čo chce obsluha dosiahnuť.



GBM60L

GBM90L

GB1TL

GB2TL

GB3TPL

GB4TL

ŠPECIFIKÁCIE

Popis	Jednotka	GBM60	GBM90	GB1T	GB2T	GB3TP	GB4T	GB5T	GB150	GB6T	GB8AT(7TL)	GB8T
Prietok oleja	lit/min	15~30	20~35	24~50	34~60	40~80	45~85	85~110	90~115	100~120	120~150	120~150
	gpm	4~8	5~9	6~13	9~16	10~21	12~22	22~29	24~30	26~32	32~40	32~40
Prevádzkový tlak oleja	bar	75~95	80~100	90~120	95~130	100~140	130~150	150~170	150~170	150~170	160~180	160~180
	psi	1,102~1,380	1,176~1,470	1,323~1,764	1,396~1,911	1,470~2,058	1,911~2,205	2,205~2,499	2,205~2,499	2,205~2,499	2,352~2,646	2,352~2,646
Uvoľnenie systému	bar	150	150	150	160	160	180	200	200	200	210	210
	psi	2,175	2,175	2,175	2,320	2,320	2,610	2,900	2,900	2,900	3,045	3,045
Úderov za minútu	bpm	800~1,400	650~1,200	550~1,100	450~1,000	475~950	480~850	450~780	420~730	420~700	350~680	320~660
Energia nárazu	joule	180	220	320	600	700	1,270	2,000	2,200	2,950	4,500	5,000
	foot-pounds	133	166	239	442	516	940	1,475	1,622	2,175	3,319	3,688
Priemer nástroja	mm	40	45	58	70	75	90	100	115	125	135	140
	inch	1.57	1.77	2.28	2.75	2.95	3.54	3.93	4.53	4.92	5.31	5.51
Priemer olejovej hadice	mm	13	13	13	13	13	19	19	25	25	25	25
	inch	1/2	1/2	1/2	1/2	1/2	3/4	3/4	1	1	1	1
Tlak plynu utesnenej zadnej hlavy	bar	14	14	14	16.3	16.3	16.3	16.3	14	16.3	16.3	16.3
	psi	203	203	203	236	236	236	236	203	236	236	236

GENERAL BREAKER



GB5TL

GB150L

GB6TL

GB8ATL(GB7TL)

GB8TL

Popis		Jednotka	GBM60	GBM90	GB1T	GB2T	GB3TP	GB4T	GB5T	GB150	GB6T	GB8AT(7TL)	GB8T
Prevádzková hmotnosť	Typ s nízkym hlukom s montážnou krytkou	kg	135	145	190	310	380	570	890	960	1,200	1,700	1,860
		lb	297	319	418	682	836	1,254	1,958	2,112	2,640	3,740	4,092
	Typ s bočnou platňou s montážnou krytkou	kg	75	86	176	324	380	613	850	920	1,280	1,800	1,980
		lb	165	189	387	713	836	1,349	1,870	2,024	2,816	3,960	4,356
Výška s nástrojom (bez montážnej krytky, krabicový typ s nízkym hlukom)	mm	988	1,082	1,205	1,384	1,451	1,789	2,043	1,984	2,264	2,411	2,477	
	inch	38.9	42.6	47.4	54.5	57.1	70.4	80.4	78.1	89.1	94.9	97.5	
85dB(A) polomer	Hranatý typ s nízkym hlukom	m	7	7	8	10	11	12	13	14	14	15	16
	Plochý bočný typ	m	12	12	13	16	18	21	31	32	33	35	37
Hmotnosť nosiča	Min / Max	ton	0.7~2.5	1.2~3	2.5~4.5	3.5~7	5~9	6~13	10~17	13~18	15~20	18~28	20~30
		lbs	1,540~5,500	1,640~6,600	5,500~9,900	7,700~15,400	11,000~19,800	13,200~28,600	22,000~37,400	28,600~39,600	33,000~44,000	39,600~61,600	44,000~66,000
	Vhodná	ton	0.7~1.2	1.2~2.4	2.5~3.5	4~7	6~8	7~12	12~15	15~17	17~19	20~23	22~25
		lbs	1,540~2,640	2,640~5,280	5,500~7,700	8,800~15,400	13,200~17,600	15,400~26,400	26,400~33,000	33,000~37,400	37,400~41,800	44,000~50,600	48,400~55,000
Objem lyžice	cbm	0.02~0.04	0.04~0.07	0.06~0.1	0.1~0.25	0.2~0.35	0.25~0.45	0.4~0.7	0.5~0.8	0.6~0.8	0.7~1.0	0.8~1.1	